Total Enclosure Multi-packing Solution

Ship with confidence when you bundle products with EDL Packaging's total enclosure Double Tight Wrap to eliminate product shifting. Using low heat to fuse perpendicular LDPE film bands, your product is tightly enclosed to create a stable shipping unit.

DOUBLE TIGHT WRAP

- Maximize your packaging material investment by eliminating excess film and "dog ears" along pack sides without the need for side seals
- Double film coverage that protects your product's damage prone corners and edges
- Double tight, multi-packaging band option eliminates the need for additional heat for temperature sensitive products
- Consistent multi-package collation for stable, stackable pallet loads for efficient shipping and warehousing

IDUSTRIES SERVED



UP TO
40%
Less film compared to traditional total enclosure shrink packaging systems



DOUBLE TIGHT WRAP

MACHINE SPECIFICATIONS

FEATURES AND OPTIONS

- Servo controlled collation conveyor
- Integrated servo controlled metering and condition belt
- Servo controlled gable folding and pushers
- Two-roll film system (single wound) with 20" diameter roll capacity
- Category III safety switches
- High efficiency low heat tunnel
- Up to 25 bags per minute
- Two year warranty on parts (excluding consumables)

TAILORED PACKAGING MACHINE DESIGNED TO MEET YOUR PRODUCT AND FACILITY NEEDS

Engineering experts work with you to understand your product, packaging, and facility needs, and design the machine to meet your requirements.

- Maximize your production floor layout with multiple "U" and "Z" line layouts available
- Engineered with flexibility to accommodate your future packaging needs
- Meet regulatory requirements and reduce product build-up and production downtime with easy-to-clean design features
- Reduces film consumption by 15-40% compared to traditional total enclosure shrink packaging



920.336.7744 sales@edlpackaging.com 1260 Parkview Rd, Green Bay WI 54304 www.edlpackaging.com